



SOVEREIGN TECHNICAL INFORMATION SHEET RENDERLITE FINISHING PLASTER

ORDER CODE: 83

Description

Sovereign Renderlite Finishing Plaster is a gypsum based plaster for use as the final coat after Sovereign Renderlite Renovating Plaster. When cured it forms a hard wall finish plaster that allows the walls to breathe.

Form Supplied: Powder
Pack Sizes: 25 kg
Colour range: Dries off white
Contains: Lime, gypsum and fine aggregate

Properties

Sovereign Renderlite has excellent adhesion and impact resistance and resists the passage of salts. Once mixed it can be re-tempered and used for up to 80 minutes minimising waste.

Usage/Preparation

Apply on to a suitably prepared background plaster such as Sovereign Renderlite, Ready Render or ordinary sand: cement plaster. It is not however suitable for use on plasterboard.

Mixing

Add Sovereign Renderlite finish to water and bring to a workable consistency. Allow the mix to rest for 5 minutes and remix adding a small quantity of water if necessary. During use Renderlite Finishing Plaster may give the appearance of going off. However this is not the case and the mix can be reworked with the trowel. Renderlite Finishing Plaster will continue to thicken and can be reworked for up to 80 minutes which should allow plenty of time for the material to be used up without waste.

Application

Apply at 1.5 to 3 mm thickness to give a smooth surface. Renderlite Finishing Plaster cannot be over polished to give a glazed surface. This is because polished plaster causes problems when painting or tiling onto normal gypsum finishes. Due to its nature the application of Renderlite Finishing Plaster feels different from normal gypsum render and this must be considered during use. Once set the plaster will be very hard and creamy white in colour.

Decoration

When the Renderlite system is used after the insertion of a DPC then it should be left as long as possible before the application of a paint coating, wallpapering must be delayed for 6 months. If tiles are to be applied then these should be fixed directly to the backing coat using one of Sovereigns powdered tile adhesives.

Practical coverage

Coverage at 1.5 mm thickness is approximately 12.5 m² per 25 kg bag.

Shelf Life and Storage

This product must be stored in a dry place, free from moisture contact. Sovereign Renderlite Finishing Plaster has a shelf life of 6 months in unopened bags. Do not store in direct contact with the ground.

General And Safety Precautions

Do not breathe dust. Avoid contact with eyes/skin. In case of contact with eyes rinse immediately with copious amounts of water and seek medical attention.

Wear suitable protective clothing/gloves and overalls (goggles if risk of splashing).

For full health and safety information see Safety Data Sheet reference number SDS 87.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice, please ensure you have the latest updated information.

SOVEREIGN

Sovereign Chemicals Limited,
Park Road, Barrow in Furness,
Cumbria.
Tel: 01229 870800
Fax: 01229 870850
Technical Support Line: 0845 603 0722
Web: www.sovchem.co.uk
Email: sales@sovchem.co.uk

TECHNICAL DATA SHEET